

# 3370 Naftrex/B



## NAFTREX/B

Oil and petrol hose

Marking:

DIN 73379 – Diameter – Germany

Coils in various lengths.

Norm	DIN 73379 march 1982 type B SAE J30
WP	10 bar
BP	30 bar
Min. temperature	-35 °C
Max. temperature hot water	+90 °C
Compound tube	NBR
Construction tube	Smooth
Color tube	Black
Compound cover	NBR
Construction cover	Textile braided
Color cover	Black
Resistance tube	E 10 B 20 E 85

## Description

Art.-no.	Ø Inner mm	Wall mm	Ø Outer mm	Bending radius mm	Weight/mtr	Length mtr.
3370032070	3,2	1,9	7	40	0,045 kg	10/20
3370035075	3,5	2,0	7,5	45	0,050 kg	10/20
3370040090	4	2,5	9	45	0,075 kg	10/20
3370045095	4,5	2,5	9,5	50	0,080 kg	10/20
3370050100	5	2,5	10	50	0,085 kg	10/20
3370055105	5,5	2,5	10,5	50	0,090 kg	10/20
3370060110	6	2,5	11	60	0,100 kg	10/20
3370070120	7	2,5	12	60	0,110 kg	10/20
3370075125	7,5	2,5	12,5	65	0,115 kg	10/20
3370080130	8	2,5	13	65	0,120 kg	10/20
3370090140	9	2,5	14	65	0,135 kg	10/20
3370115170	11,5	2,75	17	75	0,180 kg	10/20

**Application:** Extruded, textile braided fuel hose suitable for the transport of fuels with an aromatic content up to 50%. Also suitable for various other materials (coolants, water, air, liquids without oxidizing substances) with different temperature ranges per application. The Naftrex/B is used for machines and agricultural and horticultural tools.

**Remark:**

- Levering kan bestaan uit 10m en 20m lengtes gecombineerd
- Cutted length is not possible

