

Hijsbanden / Webbing Slings


















Eigenschappen

- » Volgens EN 1492-1.
- » Veiligheidsfactor 7:1.
- » Gemaakt van polyester (PES).
- » Met tonnage strepen.
- » Gestikt etiket met extra beschermfolie.
- » Met dubbele bandlaag en versterkte ogen.
- » Beschikbaar in verschillende lengtes volgens de EN standaard kleurcode.
- » Voldoet aan de Machinerichtlijn 2006/42/EG. Geleverd met testcertificaat, CE-conformiteitsverklaring en gebruiksaanwijzing.

Features

- » According to EN 1492-1.
- » Safety factor 7:1.
- » Made of polyester (PES).
- » With capacity stripes.
- » Stitched label with additional protective cover.
- » With double webbing and reinforced eyes.
- » Available in different lengths according to EN standard colour coded.
- » Complies with the Machinery Directive 2006/42/EC. Supplied with test certificate, CE declaration of conformity and operating instructions.

Specificaties / Specifications							
Ar tikelnummer	Capaciteit					Bandbreedte	Kleur
Article code	Capacity					Webbing width	Colour
	enkel / single	gestropt / choker	dubbel / double	dubbel / double	dubbel / double	mm	
	ton	ton	ton	ton	ton		
							
				7-45°	45-60°		
CO.HL.01	1.0	0.8	2.0	1.4	1.0	30	
CO.HL.02	2.0	1.6	4.0	2.8	2.0	60	
CO.HL.03	3.0	2.4	6.0	4.2	3.0	90	
CO.HL.04	4.0	3.2	8.0	5.6	4.0	120	
CO.HL.05	5.0	4.0	10.0	7.0	5.0	150	
CO.HL.06	6.0	4.8	12.0	8.4	6.0	180	
CO.HL.08	8.0	6.4	16.0	11.2	8.0	210	
CO.HL.10	10.0	8.0	20.0	14.0	10.0	240	
CO.HL.12	12.0	9.6	24.0	16.8	12.0	270	

Specificaties / Specifications				
Ar tikelnummer	Capaciteit	Bandbreedte	Veiligheidsfactor	Kleur
Article code	Capacity	Webbing width	Safety factor	Colour
	ton	mm		
CO.EHB.0075	0.75	25	5:1	
CO.EHB.0100	1.0	30	7:1	