

Camlock couplings SS316

Camlock RVS koppelingen



Male adapter type A - MIL A-A-59326A with female BSPP thread
 Camlock mannelijk - type A met binnendraad RVS

Part-No.	Material	WP	Dimension	Thread	
A050SS	SS316/CF8M	10 bar	DN15	1/2"	
A075SS	SS316/CF8M	10 bar	DN20	3/4"	
A100SS	SS316/CF8M	10 bar	DN25	1"	
A125SS	SS316/CF8M	10 bar	DN32	1 1/4"	
A150SS	SS316/CF8M	10 bar	DN40	1 1/2"	
A200SS	SS316/CF8M	10 bar	DN50	2"	
A250SS	SS316/CF8M	10 bar	DN65	2 1/2"	
A300SS	SS316/CF8M	10 bar	DN80	3"	
A400SS	SS316/CF8M	7 bar	DN100	4"	
A500SS	SS316/CF8M	5 bar	DN125	5"	
A600SS*	SS316/CF8M	5 bar	DN150	6"	

Camlock couplings SS316

Camlock RVS koppelingen

Male adapter type A - MIL A-A-59326A with female NPT thread



Part-No.	Material	WP	Dimension	Thread	
A050SS-NPT	SS316/CF8M	10 bar	DN15	1/2"	
A075SS-NPT	SS316/CF8M	10 bar	DN20	3/4"	
A100SS-NPT	SS316/CF8M	10 bar	DN25	1"	
A125SS-NPT	SS316/CF8M	10 bar	DN32	1 1/4"	
A150SS-NPT	SS316/CF8M	10 bar	DN40	1 1/2"	
A200SS-NPT	SS316/CF8M	10 bar	DN50	2"	
A250SS-NPT	SS316/CF8M	10 bar	DN65	2 1/2"	
A300SS-NPT	SS316/CF8M	10 bar	DN80	3"	
A400SS-NPT	SS316/CF8M	7 bar	DN100	4"	

Camlock couplings SS316

Camlock RVS koppelingen



Female coupler type B - MIL A-A-59326A with male BSPT thread - NBR gasket

Camlock Vrouwelijk - type B met buitendraad RVS

Part-No.	Material	WP	Dimension	Thread	
B050SS2	SS316/CF8M	10 bar	DN15	1/2"	
B075SS	SS316/CF8M	10 bar	DN20	3/4"	
B100SS	SS316/CF8M	10 bar	DN25	1"	
B125SS	SS316/CF8M	10 bar	DN32	1 1/4"	
B150SS	SS316/CF8M	10 bar	DN40	1 1/2"	
B200SS	SS316/CF8M	10 bar	DN50	2"	
B250SS	SS316/CF8M	10 bar	DN65	2 1/2"	
B300SS	SS316/CF8M	10 bar	DN80	3"	
B400SS	SS316/CF8M	7 bar	DN100	4"	
B500SS	SS316/CF8M	5 bar	DN125	5"	
B600SS	SS316/CF8M	5 bar	DN150	6"	



Female coupler type B - MIL A-A-59326A with male BSPT thread - System Self-Lock - NBR gasket

Camlock vrouwelijk - type B met buitendraad RVS - Self-Lock

Part-No.	Material	WP	Dimension	Thread	
B200SS-SLL	SS316/CF8M	10 bar	DN50	2"	
B300SS-SLL	SS316/CF8M	10 bar	DN80	3"	
B400SS-SLL	SS316/CF8M	7 bar	DN100	4"	

Camlock couplings SS316

Camlock RVS koppelingen

Female coupler type B - MIL A-A-59326A with male NPT thread - NBR gasket



Part-No.	Material	WP	Dimension	Thread	
B075SS-NPT	SS316/CF8M	10 bar	DN20	3/4"	
B100SS-NPT	SS316/CF8M	10 bar	DN25	1"	
B125SS-NPT	SS316/CF8M	10 bar	DN32	1 1/4"	
B150SS-NPT	SS316/CF8M	10 bar	DN40	1 1/2"	
B200SS-NPT	SS316/CF8M	10 bar	DN50	2"	
B250SS-NPT	SS316/CF8M	10 bar	DN65	2 1/2"	
B300SS-NPT	SS316/CF8M	10 bar	DN80	3"	
B400SS-NPT	SS316/CF8M	7 bar	DN100	4"	

Female coupler type B - MIL A-A-59326A with male BSPT thread - Type Security Lock - NBR gasket

Camlock vrouwelijk - type B met buitendraad RVS - Security-Lock



NEW

Part-No.	Material	WP	Dimension	Thread	
B075SECURITY	SS316/CF8M	10 bar	DN20	3/4"	
B100SECURITY	SS316/CF8M	10 bar	DN25	1"	
B125SECURITY	SS316/CF8M	10 bar	DN32	1 1/4"	
B150SECURITY	SS316/CF8M	10 bar	DN40	1 1/2"	
B200SECURITY	SS316/CF8M	10 bar	DN50	2"	
B300SECURITY	SS316/CF8M	10 bar	DN80	3"	
B400SECURITY	SS316/CF8M	7 bar	DN100	4"	

No stock item!

Camlock couplings SS316

Camlock RVS koppelingen



Female coupler type C - MIL A-A-59326A with grooved hose-shank - NBR gasket

Camlock vrouwelijk - type C met slangpilaar RVS

Part-No.	Material	WP	Dimension	Shank	
C050SS2	SS316/CF8M	10 bar	DN15	13mm	
C075SS	SS316/CF8M	10 bar	DN20	21mm	
C100SS	SS316/CF8M	10 bar	DN25	27mm	
C125SS	SS316/CF8M	10 bar	DN32	34mm	
C150SS	SS316/CF8M	10 bar	DN40	40mm	
C200SS	SS316/CF8M	10 bar	DN50	51mm	
C200x150SS	SS316/CF8M	10 bar	DN50	40mm	
C250SS	SS316/CF8M	10 bar	DN65	64mm	
C300SS	SS316/CF8M	10 bar	DN80	76mm	
C400SS	SS316/CF8M	7 bar	DN100	103mm	
C500SS	SS316/CF8M	5 bar	DN125	128mm	
C600SS	SS316/CF8M	5 bar	DN150	152mm	



Female coupler type C - MIL A-A-59326A with grooved hose-shank - System Self-Lock - NBR gasket

Camlock vrouwelijk - type C met slangpilaar RVS Self-Lock

Part-No.	Material	WP	Dimension	Shank	
C200SS-SLL	SS316/CF8M	10 bar	DN50	51mm	
C300SS-SLL	SS316/CF8M	10 bar	DN80	76mm	
C400SS-SLL	SS316/CF8M	7 bar	DN100	103mm	

Camlock couplings SS316

Camlock RVS koppelingen

Female coupler type C - MIL A-A-59326A with grooved hose-shank - Type Security Lock - NBR gasket

Camlock vrouwelijk - type C met slangpilaar RVS - Security Lock

NEW



No stock item!

Part-No.	Material	WP	Dimension	Shank	
C075SECURITY	SS316/CF8M	10 bar	DN19	21mm	
C100SECURITY	SS316/CF8M	10 bar	DN25	27mm	
C125SECURITY	SS316/CF8M	10 bar	DN32	34mm	
C150SECURITY	SS316/CF8M	10 bar	DN40	40mm	
C200SECURITY	SS316/CF8M	10 bar	DN50	51mm	
C300SECURITY	SS316/CF8M	10 bar	DN80	76mm	
C400SECURITY	SS316/CF8M	7 bar	DN100	103mm	

Camlock couplings SS316

Camlock RVS koppelingen



Female coupler type D - MIL A-A-59326A with female BSPP thread - NBR gasket

Camlock vrouwelijk - type D met binnendraad RVS

Part-No.	Material	WP	Dimension	Thread	
D050SS2	SS316/CF8M	10 bar	DN15	1/2"	
D075SS	SS316/CF8M	10 bar	DN20	3/4"	
D100SS	SS316/CF8M	10 bar	DN25	1"	
D125SS	SS316/CF8M	10 bar	DN32	1 1/4"	
D150SS	SS316/CF8M	10 bar	DN40	1 1/2"	
D200SS	SS316/CF8M	10 bar	DN50	2"	
D250SS	SS316/CF8M	10 bar	DN65	2 1/2"	
D300SS	SS316/CF8M	10 bar	DN80	3"	
D400SS	SS316/CF8M	7 bar	DN100	4"	
D500SS	SS316/CF8M	5 bar	DN125	5"	
D600SS	SS316/CF8M	5 bar	DN150	6"	



Female coupler type D - MIL A-A-59326A with female BSPP thread - System Self-Lock - NBR gasket

Camlock vrouwelijk - type D met binnendraad RVS - Self-Lock

Part-No.	Material	WP	Dimension	Thread	
D200SS-SLL	SS316/CF8M	10 bar	DN50	2"	
D300SS-SLL	SS316/CF8M	10 bar	DN80	3"	
D400SS-SLL	SS316/CF8M	7 bar	DN100	4"	

Camlock couplings SS316

Camlock RVS koppelingen

Female coupler type D - MIL A-A-59326A with female NPT thread - NBR gasket



Part-No.	Material	WP	Dimension	Thread	
D075SS-NPT	SS316/CF8M	10 bar	DN20	3/4"	
D100SS-NPT	SS316/CF8M	10 bar	DN25	1"	
D125SS-NPT	SS316/CF8M	10 bar	DN32	1 1/4"	
D150SS-NPT	SS316/CF8M	10 bar	DN40	1 1/2"	
D200SS-NPT	SS316/CF8M	10 bar	DN50	2"	
D250SS-NPT	SS316/CF8M	10 bar	DN65	2 1/2"	
D300SS-NPT	SS316/CF8M	10 bar	DN80	3"	
D400SS-NPT	SS316/CF8M	7 bar	DN100	4"	

Female coupler type D - MIL A-A-59326A with female BSP thread - Type Security Lock - NBR gasket

Camlock vrouwelijk - type D met binnendraad RVS - Security Lock



NEW

Part-No.	Material	WP	Dimension	Thread	
D075SECURITY	SS316/CF8M	10 bar	DN20	3/4"	
D100SECURITY	SS316/CF8M	10 bar	DN25	1"	
D125SECURITY	SS316/CF8M	10 bar	DN32	1 1/4"	
D150SECURITY	SS316/CF8M	10 bar	DN40	1 1/2"	
D200SECURITY	SS316/CF8M	10 bar	DN50	2"	
D300SECURITY	SS316/CF8M	10 bar	DN80	3"	
D400SECURITY	SS316/CF8M	7 bar	DN100	4"	

No stock item!

Camlock couplings SS316

Camlock RVS koppelingen



Male adapter type E - MIL A-A-59326A with grooved hose-shank

Camlock mannelijk - type E met slangpilaar RVS

Part-No.	Material	WP	Dimension	Shank	
E050SS	SS316/CF8M	10 bar	DN15	13mm	
E075SS	SS316/CF8M	10 bar	DN20	21mm	
E100SS	SS316/CF8M	10 bar	DN25	27mm	
E125SS	SS316/CF8M	10 bar	DN32	34mm	
E150SS	SS316/CF8M	10 bar	DN40	40mm	
E200SS	SS316/CF8M	10 bar	DN50	51mm	
E250SS	SS316/CF8M	10 bar	DN65	64mm	
E300SS	SS316/CF8M	10 bar	DN80	76mm	
E400SS	SS316/CF8M	7 bar	DN100	103mm	
E500SS	SS316/CF8M	5 bar	DN125	128mm	
E600SS	SS316/CF8M	5 bar	DN150	152mm	

Camlock couplings SS316

Camlock RVS koppelingen

Male adapter type F - MIL A-A-59326A with male BSPT thread

Camlock mannelijk - type F met buitendraad RVS



Part-No.	Material	WP	Dimension	Thread
F050SS	SS316/CF8M	10 bar	DN15	1/2"
F075SS	SS316/CF8M	10 bar	DN20	3/4"
F100SS	SS316/CF8M	10 bar	DN25	1"
F125SS	SS316/CF8M	10 bar	DN32	1 1/4"
F150SS	SS316/CF8M	10 bar	DN40	1 1/2"
F200SS	SS316/CF8M	10 bar	DN50	2"
F250SS	SS316/CF8M	10 bar	DN65	2 1/2"
F300SS	SS316/CF8M	10 bar	DN80	3"
F400SS	SS316/CF8M	7 bar	DN100	4"
F500SS	SS316/CF8M	5 bar	DN125	5"
F600SS	SS316/CF8M	5 bar	DN150	6"

Male adapter type F - MIL A-A-59326A with male NPT thread



Part-No.	Material	WP	Dimension	Thread
F100SS-NPT	SS316/CF8M	10 bar	DN25	1"
F125SS-NPT	SS316/CF8M	10 bar	DN32	1 1/4"
F150SS-NPT	SS316/CF8M	10 bar	DN40	1 1/2"
F200SS-NPT	SS316/CF8M	10 bar	DN50	2"
F250SS-NPT	SS316/CF8M	10 bar	DN65	2 1/2"
F300SS-NPT	SS316/CF8M	10 bar	DN80	3"
F400SS-NPT	SS316/CF8M	7 bar	DN100	4"

Camlock couplings SS316

Camlock RVS koppelingen



Dust cap type DC - MIL A-A-59326A - NBR gasket

Camlock vrouwelijk kap - type DC RVS

Part-No.	Material	WP	Dimension
DC050SS2	SS316/CF8M	10 bar	DN15
DC075SS	SS316/CF8M	10 bar	DN20
DC100SS	SS316/CF8M	10 bar	DN25
DC125SS	SS316/CF8M	10 bar	DN32
DC150SS	SS316/CF8M	10 bar	DN40
DC200SS	SS316/CF8M	10 bar	DN50
DC250SS	SS316/CF8M	10 bar	DN65
DC300SS	SS316/CF8M	10 bar	DN80
DC400SS	SS316/CF8M	7 bar	DN100
DC500SS	SS316/CF8M	5 bar	DN125
DC600SS	SS316/CF8M	5 bar	DN150



Dust cap type DC - MIL A-A-59326A - System Self-Lock - NBR gasket

Camlock vrouwelijk kap - type DC RVS - Self-Lock

Part-No.	Material	WP	Dimension
DC200SS-SLL	SS316/CF8M	10 bar	DN50
DC300SS-SLL	SS316/CF8M	10 bar	DN80
DC400SS-SLL	SS316/CF8M	7 bar	DN100

Camlock couplings SS316

Camlock RVS koppelingen

Dust cap type DC - MIL A-A-59326A - Type Security Lock - NBR gasket

Camlock vrouwelijk kap - type DC RVS - Security Lock

NEW



No stock item!

Part-No.	Material	WP	Dimension
DC100SECURITY	SS316/CF8M	10 bar	DN25
DC125SECURITY	SS316/CF8M	10 bar	DN32
DC150SECURITY	SS316/CF8M	10 bar	DN40
DC200SECURITY	SS316/CF8M	10 bar	DN50
DC300SECURITY	SS316/CF8M	10 bar	DN80
DC400SECURITY	SS316/CF8M	7 bar	DN100

Dust plug type DP - MIL A-A-59326A

Camlock mannelijke plug - type DP RVS



Part-No.	Material	WP	Dimension
DP050SS	SS316/CF8M	10 bar	DN15
DP075SS	SS316/CF8M	10 bar	DN20
DP100SS	SS316/CF8M	10 bar	DN25
DP125SS	SS316/CF8M	10 bar	DN32
DP150SS	SS316/CF8M	10 bar	DN40
DP200SS	SS316/CF8M	10 bar	DN50
DP250SS	SS316/CF8M	10 bar	DN65
DP300SS	SS316/CF8M	10 bar	DN80
DP400SS	SS316/CF8M	7 bar	DN100
DP500SS	SS316/CF8M	5 bar	DN125
DP600SS	SS316/CF8M	5 bar	DN150

Camlock couplings SS316

Camlock RVS koppelingen



Male - butweld camlock - MIL A-A-59326A

Camlock mannelijke aanslas

Par t-No.	Material	WP	Dimension	BW (IDxOD)	
F050SSBW	SS316/CF8M	10 bar	DN15	14,4 x 21,3	
F075SSBW	SS316/CF8M	10 bar	DN20	20 x 26,7	
F100SSBW	SS316/CF8M	10 bar	DN25	26 x 33,4	
F125SSBW	SS316/CF8M	10 bar	DN32	34 x 42,2	
F150SSBW	SS316/CF8M	10 bar	DN40	39 x 48,3	
F200SSBW	SS316/CF8M	10 bar	DN50	51 x 60,3	
F250SSBW	SS316/CF8M	10 bar	DN65	66,5 x 76,1	
F300SSBW	SS316/CF8M	10 bar	DN80	78 x 88,9	
F400SSBW	SS316/CF8M	7 bar	DN100	102 x 114,3	
F500SSBW	SS316/CF8M	5 bar	DN125	129,8 x 141,3	
F600SSBW	SS316/CF8M	5 bar	DN150	150,8 x 168,3	



Male flanged camlock coupling - MIL A-A-59326A

Camlock mannelijk koppeling geflensd

Par t-No.	Material	WP	Dimension	Flange	
100ANP	SS316/CF8M	10 bar	DN25	PN 10/16	
125ANP	SS316/CF8M	10 bar	DN32	PN 10/16	
150ANP	SS316/CF8M	10 bar	DN40	PN 10/16	
200ANP	SS316/CF8M	10 bar	DN50	PN 10/16	
250ANP	SS316/CF8M	10 bar	DN65	PN 10/16	
300ANP	SS316/CF8M	10 bar	DN80	PN 10/16	
400ANP	SS316/CF8M	10 bar	DN100	PN 10/16	

Camlock couplings SS316

Camlock RVS koppelingen

Female - butweld camlock - MIL A-A-59326A - NBR gsket

Camlock vrouwelijke aanslas



Part-No.	Material	WP	Dimension	BW (IDxOD)	
B050SSBW	SS316/CF8M	10 bar	DN15	14,4 x 21,3	
B075SSBW	SS316/CF8M	10 bar	DN20	20 x 26,7	
B100SSBW	SS316/CF8M	10 bar	DN25	26 x 33,4	
B125SSBW	SS316/CF8M	10 bar	DN32	34 x 42,2	
B150SSBW	SS316/CF8M	10 bar	DN40	39 x 48,3	
B200SSBW	SS316/CF8M	10 bar	DN50	51 x 60,3	
B250SSBW	SS316/CF8M	10 bar	DN65	66,5 x 76,1	
B300SSBW	SS316/CF8M	10 bar	DN80	78 x 88,9	
B400SSBW	SS316/CF8M	7 bar	DN100	102 x 114,3	
B500SSBW	SS316/CF8M	5 bar	DN125	129,8 x 141,3	
B600SSBW	SS316/CF8M	5 bar	DN150	150,8 x 168,3	

Female flanged camlock coupling - MIL A-A-59326A - NBR gasket

Camlock vrouwelijk koppeling geflensd



Part-No.	Material	WP	Dimension	Flange	
100CNP	SS316/CF8M	10 bar	DN25	PN 10/16	
125CNP	SS316/CF8M	10 bar	DN32	PN 10/16	
150CNP	SS316/CF8M	10 bar	DN40	PN 10/16	
200CNP	SS316/CF8M	10 bar	DN50	PN 10/16	
250CNP	SS316/CF8M	10 bar	DN65	PN 10/16	
300CNP	SS316/CF8M	10 bar	DN80	PN 10/16	
400CNP	SS316/CF8M	10 bar	DN100	PN 10/16	

Camlock couplings SS316

Camlock RVS koppelingen



Type A-A



Type D-A

Camlock adapter - MIL A-A-59326A

Camlock adapter

Part-No.	Material	Typ	WP	DN1	DN2
AA100100SS	SS316/CF8M	A-A	10 bar	DN25	DN25
AA200200SS	SS316/CF8M	A-A	10 bar	DN50	DN50
AA300300SS	SS316/CF8M	A-A	10 bar	DN80	DN80
DA300200SS	SS316/CF8M	D-A	10 bar	DN80	DN50
DA400300SS	SS316/CF8M	D-A	10 bar	DN100	DN80

Other sizes and adapter available



Male adapter type A - EN14420-7 with female BSPP thread - flat sealed - PTFE thread gasket

Camlock adapter mannelijk type A

Part-No.	Material	WP	Dimension	Thread
A075DINSS	SS 1.4408	10 bar	DN19	3/4"
A100DINSS	SS 1.4408	10 bar	DN25	1"
A125DINSS	SS 1.4408	10 bar	DN32	1 1/4"
A150DINSS	SS 1.4408	10 bar	DN40	1 1/2"
A200DINSS	SS 1.4408	10 bar	DN50	2"
A250DINSS	SS 1.4408	10 bar	DN65	2 1/2"
A300DINSS	SS 1.4408	10 bar	DN80	3"
A400DINSS	SS 1.4408	7 bar	DN100	4"