


Delivery Hose Couplings

Seal: Nitrile rubber black / white
Fluoro rubber - Stainless steel



Aluminium light alloy	Messing copper alloy	Edelstahl stainless steel
--------------------------	-------------------------	------------------------------

Storz Size	KA (mm) Lug	D (mm) Diameter	L (mm) Length	Weight (kg)	Bemerkung Remark	Ident-No.	Euro
25-D	31	15/13	55	0,09	Sägezahn	12-031013-10	
		15	60	0,27		12-031013-30	
		21/19	55	0,10	Sägezahn	12-031019-10	
		21/19	55	0,09	1 Rille / 1 groove	12-031019-18	
		21/19	60	0,28	Sägezahn	12-031019-30	
		21/19	55	0,26	Sägezahn	12-031019-43	
		25	53	0,09	DIN 14 301	12-031025-10	
		25	53	0,28		12-031025-30	
		25	53	0,26		12-031025-43	
45	59	45	75	0,28		11-059045-15	
52-C	66	40	70	0,37	Schweizer Norm	11-066040-15	
		42	55	0,33	DIN 14 332	11-066042-15	
		42	55	0,94		11-066042-35	
		45	70	0,36	Italien. Norm	11-066045-15	
		52	55	0,33	DIN 14 302	11-066052-15	
		52	55	0,31	gegossen / cast *	11-066052-25	
		52	75	0,96	DIN 86 202	11-066052-35	
		52	90	0,95		12-066052-43	
		55	70	0,36	Schweizer Norm	11-066055-15	
65	81	52	60	0,44		11-081052-15	
		65	60	0,43		11-081065-15	
		75	65	0,46		11-081075-15	
75-B	89	65	85	0,57		11-089065-15	
		70	75	0,58	Italien. Norm	11-089070-15	
		75	60	0,55	DIN 14 303	11-089075-15	
		75	60	0,51	gegossen / cast *	11-089075-25	
		75	85	1,65	DIN 86 203	11-089075-35	
		75	105	1,79		12-089075-43	
		75	80	0,57	Schweizer Norm	11-089075-19	
100	115	100	85	0,99		11-115100-15	
110-A	133	100	110	1,48		11-133100-10	
		110	110	1,37		11-133110-10	