

## 3225 Ariacord®/ Yellow



### ARIACORD®/YELLOW

Air pressure/waterhose

for heavy duty applications. Oil mist resistant. UV and ageing resistant cover.

Marking:

 Ariacord® Air/Water – Luft/Wasser PN 25 bar – PB 80 bar

Norm	EN ISO 1307:2008
WP	25 bar
BP	80 bar
Min. temperature	-30 °C
Max. temperature	+80 °C
Compound tube	EPDM
Construction tube	Smooth
Color tube	Black
Compound cover	EPDM
Construction cover	Fabric finish
Color cover	Yellow
Resistance cover	Ageing resistant Weather resistant
Reinforcements	Textile plies

## Description

Art.-no.	Ø Inner mm	Wall mm	Ø Outer mm	Bending radius mm	Weight/mtr	Length mtr.
3225032000	32	7,0	46	260	1,200 kg	40
3225038000	38	7,0	52	350	1,400 kg	40
3225050000	51	7,5	66	400	1,900 kg	20/40
3225063000	63,5	9,5	82,5	480	2,900 kg	40
3225075000	76	9,5	95	610	3,300 kg	40

**Application:** High quality, robust, thick walled flexible rubber hose for heavy duty applications in the industry, maintenance workshops, tunnel construction, infrastructure and on construction sites. Suitable for transport of water and air. The hose is also resistant to oil mist.

**Remark:**

- Cutted length possible