

# Drinkwaterslang

Flexibele TPE Drinkwaterslang



## Eigenschappen

Materiaal binnenwand	TPE
Type inlagen	NTS Plus
Temperatuurbereik °C	-30°C/+70°C
Norm	KTW-A, DVGW W270, European Regulation 10/2011 (simulants A-B-C-D1)

Art. nr.	Inwendige (mm)	ØUitwendige Ø (mm)	Max. werkdruk (bar)	Min. barstdruk (bar)	Wanddikte (mm)	Min. buigradius (mm)	Rollengte (mtr)	Gewicht (kg)
35002513	12.3	17.5	10	30	2.6	70	25	0.11
35000013	12.3	17.5	10	30	2.6	70	50	0.11
35002519	18.7	25.7	10	30	3.5	90	25	0.22
35000019	18.7	25.7	10	30	3.5	90	50	0.22
35002525	24.8	32.8	9	27	4	110	25	0.32

KTW-A en DVGW W270 gecertificeerde TPE drinkwaterslang. De slang is gemaakt in overeenstemming met European Regulation 10/2011 (simulants A-B-C-D1) . Ook geschikt om te gebruiken bij dranktaps in café's, beurzen, evenementen en festivals. Niet-toxische en weermakervrije gepatenteerde slang, extreem flexibel en resistent.