

## Pers plug type 360



### Specifications

Material	Aluminium/Steel
Temperature	<60 (°C)

### Description

Press plugs are used for the temporary pressure-resistant sealing and pressure testing of all types of pipelines, such as gas, water, and oil lines (steel, cast iron, plastic, etc.).

The press plug is placed in the pipe. By tightening the nut on the threaded central passage, the rubber ring(s) are pressed against the pipe wall by the top and bottom plates. This causes the pressure stop to clamp shut and seal the pipe. Depending on the pressure and diameter, one or more rubber rings or a rubber cylinder are used.

### Assets

- Suitable for pressures up to 100 bar (depending on type).
- Wide range of diameters from 14 to 2000 mm.
- Types 350 and 360 equipped with a stamping plate for securing.
- Available with/without through bore and ball valve, and with/without pressure gauge.
- Various types/versions of press plugs available for different pressures and applications\*.

*\*We can determine the type of press plug in consultation, based on your requirements and the work to be performed.*

Size	
DN 20	Single washer
DN 25	Single washer
DN 30	Single washer
DN 35	Single washer
DN 40	Single washer
DN 50	Single washer
DN 55	Single washer
DN 60	Single washer
DN 65	Single washer
DN 70	Single washer
DN 80	Single washer
DN 100	Single washer
DN 110	Single washer
DN 125	Single washer
DN 140	Single washer
DN 150	Single washer
DN 160	Single washer
DN 200	Single washer
DN 210	Single washer
DN 250	Single washer
DN 260	Single washer
DN 300	Single washer
DN 310	Single washer
DN 350	Single washer
DN 400	Single washer
DN 450	
DN 500	
DN 600	
DN 700	
DN 800	
DN 900	
DN 1000	
DN 1100	
DN 1200	