

Hosebun™



Description

Hosebuns are durable, innovative and purpose-designed solutions for supporting, suspending and organizing hoses and cables. They are used worldwide across a wide range of industries, from manufacturing to shipping. Anywhere safety, order and efficiency matter.

The unique Hosebun™ saddle is made from high-quality polyurethane, a strong and wear-resistant material that provides optimal support for both light and heavy hoses. Its curved, load-bearing shape evenly distributes weight and pressure, preventing kinks, sagging and damage. This significantly extends the service life of hoses and cables while maintaining an unrestricted, consistent flow of air, water or other media. Whether you are working with hydraulic hoses, fuel lines, air or water systems, Hosebun™ offers reliable support in every situation. The system is easy to install and suitable for both permanent installations and temporary setups.

With Hosebun™, you not only prevent damage and reduce maintenance costs but also improve workplace safety and overall operational efficiency. It is the professional solution for anyone who values reliability, durability and ease of use.

Products

Outside diameter	Length	Work Load Limit WWL	Inside diameter	Suspension Height
1.22" / 31 mm	16" / 40 cm	1.100 Lbs / 500 kg		
1.5" / 38 mm	16" / 40 cm	1.100 Lbs / 500 kg		
2" / 50 mm	16" / 40 cm	1.100 Lbs / 500 kg	1" / 25 mm	
2.25" / 57 mm	17.5" / 45 cm	1.100 Lbs / 500 kg	1.25" / 32 mm	
2.5" / 63 mm	19.5" / 49.5 cm	1.100 Lbs / 500 kg	1.5" / 38 mm	
3" / 75 mm	18" / 46 cm	1.100 Lbs / 500 kg	2" / 50 mm	
3" / 75 mm	18" / 46 cm	2.200 Lbs / 1.000 Kgs	2" / 50 mm	
3" / 75 mm	12" / 30.5 cm	1.100 Lbs / 500 kg	3" / 75 mm	
3" / 75 mm	12" / 30.5 cm	2.200 Lbs / 1.000 Kgs	2" / 50 mm	18.9" / 48 cm
3" / 75 mm	12" / 30.5 cm	2.200 Lbs / 1.000 Kgs	2" / 50 mm	19.7" / 50 cm
3" / 75 mm	18" / 46 cm	2.200 Lbs / 1.000 Kgs	2" / 50 mm	19.7" / 50 cm
3.6" / 92 mm	12.75" / 32.5 cm	1.100 Lbs / 500 Kgs	2.5" / 63 mm	
3.6" / 92 mm	12.75" / 32.5 cm	2.200 Lbs / 1.000 Kgs	2.5" / 63 mm	
4.1" / 105 mm	12.75" / 32.5 cm	2.200 Lbs / 1.000 Kgs	3" / 75 mm	18.9" / 48 cm
4.1" / 105 mm	12.75" / 32.5 cm	2.200 Lbs / 1.000 Kgs	3" / 75 mm	19.7" / 50 cm
5.1" / 130 mm	11.5" / 29 cm	2.200 Lbs / 1.000 Kgs	4" / 100 mm	18.9" / 48 cm
5.1" / 130 mm	11.5" / 29 cm	2.200 Lbs / 1.000 Kgs	4" / 100 mm	19.7" / 50 cm
6.3" / 160 mm	21.5" / 55 cm	6.614 Lbs / 3.000 Kgs	5" / 127 mm	
6.5" / 165 mm	21.5" / 55 cm	6.614 Lbs / 3.000 Kgs	5" / 127 mm	
8" / 200 mm	21.5" / 55 cm	6.614 Lbs / 3.000 Kgs	6" / 150 mm	
10" / 250 mm	30.5" / 77.5 cm	8.818 Lbs / 4.000 Kgs		
14" / 360 mm	40.75" / 103.5 cm	11.023 Lbs / 5.000 kg	14" / 360 mm	
14" / 360 mm	40.75" / 103.5 cm	11.023 Lbs / 5.000 kg	12" / 300 mm	