Hammer Union Fig. 1502 NPT Female Thread with NBR Gasket



Properties

Material	AISI4130 Staal
Coupling type	Coupling with female thread
Thread type	NPT Female thread

Art. nr.	Coupler size (inch/mm)	Working pressure (bar)	Weight (kg)
4645432	2" (DN50)	1035	9
4645428	3" (DN80)	1035	18
4645431	4" (DN100)	1035	32

Description

Hammer Unions are designed as robust high-pressure streamline connectors. They are commonly found in chemical plants, on dredgers, in strip mines and in the oil industry.
The color coding system on Hammer Unions represents the different configurations and pressure ratings.

WECO figure 1502 is used on mud lines, manifold service and truck mounting applications running air, water, oil, gas or mud up till 1035 BAR.
This WECO coupling has the standard red color.

Our couplings have a double paint coating to ensure a longer colour identification.

	Standard Service		Pipe Size (in.)									End Connection
Fig No.	CWP SUB	Test NUT	1	1¼	1½	2	2½	3	4	6	8	
100	1,000	1,500				✓	✓	✓	✓	✓	✓	T
200	2,000	3,000	✓	✓	✓	✓	✓	✓	✓	✓		T/BW
202	2,000	3,000							✓			T
206	2,000	3,000	✓	✓	✓	✓	✓	✓	✓	✓		T/BW
211	2,000	3,000	✓			✓						T/BW
300	2,000	3,000	✓			✓	✓	✓	✓			T
301	3,000	4,500	✓			✓		✓				T
400	4,000	6,000				✓		✓	✓			T/BW
600	6,000	9,000	✓		✓	✓		✓	✓			T/BW
602	6,000	9,000	✓		✓	✓		✓	✓			T/BW
607	6,000	9,000			✓	✓						T
1002	10,000	15,000	✓		✓	✓		✓	✓			T/BW
1502	15,000	22,500				✓		✓				T/BW